

**METHOD FOR PROCESSING CELLULOSIC FIBER WEB OR ITS SEWED PRODUCT**

Patent Number: JP6346370  
Publication date: 1994-12-20  
Inventor(s): YAMADA HIROO; others: 01  
Applicant(s):: UNITIKA LTD  
Requested Patent: ☒ JP6346370  
Application Number: JP19930154235 19930531  
Priority Number(s):  
IPC Classification: D06M13/52 ; D06C23/00 ; D06M13/127  
EC Classification:  
Equivalents:

**Abstract**

**PURPOSE:** To give creases excellent in washing resistance to a cellulosic fiber- containing web or its sewed product by giving creases or three-dimensional patterns to the cellulosic fiber-containing web or its sewed product and subsequently applying a crosslinking reaction to the web or its sewed product with gaseous formaldehyde.

**CONSTITUTION:** A cellulosic fiber-containing web or its sewed product is subjected to a creasing process with e.g. a washer-processing machine, allowed to stand in a constant temperature and moisture chamber for 24hr for the uniform adjustment of the water content, exposed to formaldehyde gas in a gaseous phase with a gaseous phase processing machine, and subsequently thermally treated for the formation of crosslinking bonds between the cellulose molecules and the formaldehyde, thus giving creases or three-dimensional patterns excellent in washing resistance to the web or its sewed product.

Data supplied from the esp@cenet database - 12